

DYNAMIX 4-IN-1 PREMIUM UNDERLAY

CUSHION | MOISTURE | SOUND | INSULATION

Dynamix 4-in-1 premium underlayment provides an excellent base cushion that supports the floor for optimal long term performance and is suitable for use with all laminate and engineered wood floors.

CUSHION / BASE SUPPORT

Optimal product support for the glueless installation systems found on laminate and engineered wood floors (compression deflection value of 7.5 PSI).

MOISTURE PROTECTION

Closed-cell polypropylene with pre-attached vapor barrier and a patented 3" lip and tape for increased moisture protection and ease of installation over any subfloor type (0.04 water vapor transmission¹).

SOUND REDUCTION

STC = 74², IIC = 72³

INSULATION PROPERTIES

4.0 R value⁴

ODORLESS, NON-ALLERGENIC, NON TOXIC AND NATURALLY ANTI-MICROBIAL

Dynamix is odorless, non-allergenic and non-toxic. Its closed cell makeup makes it naturally anti-microbial, without the use of additional chemicals.

SPECIFICATIONS

ROLL WIDTH X LENGTH	3.33' X 40'
ROLL COVERAGE 100 SF	100 SF
COMPRESSION DEFLECTION 7.5 PSI	7.5 PSI
WATER VAPOR TRANSMISSION 0.04	0.04
SOUND TRANSMISSION CLASS (STC) 742	74 ²
IMPACT INSULATION CLASS (IIC) 723	72 ³

1. ASTM E96
2. ASTM E90 - 6" concrete slab with drop ceiling installation
3. ASTM E492 - 6" concrete slab with drop ceiling installation
4. Based on 1" thickness

PRICING

BY THE ROLL (100 SF)	\$0.25/SF
BY THE PALLET (60 ROLLS - 6,000 SF)	\$0.21/SF
BY THE TRUCK (3,120 ROLLS - 312,00 SF)	\$0.18/SF

All prices in USD, FOB Vius' warehouse



MADE IN THE USA



FROM RECYCLED MATERIALS

Vius, Inc. P 800.769.5405

PO Box 6808 Annapolis, MD 21401

viusflooring.com